



# HUBER+SUHNER®

## DC-SET

### FOR WIRELESS COMMUNICATION



#### DC-Set for Active Antenna

##### Technical Data

##### Power Supply

Input	AC 100 – 240 V 50/60 Hz, 350 mA
Output	12 V / 1300 mA
CE tested	

Including cable RG 174 (2.0 m) with SMA male.

##### Bias Tee

Frequency range	2400 - 2700 MHz
Impedance	50 Ω
VSWR	1.5
Isolation	25 dB
Insertion Loss	0.5 dB
Max. power	1 W (CW) at 25°C
RF input	SMA female
RF and DC output	SMA female
DC input	SMA female
Dimensions	101 x 95 x 32 mm (3.98" x 3.74" x 1.26")

##### Power Cord

T11 Euro (black)	
1-15P NEMA (black)	

##### Available Type

Available Type	Article no.
9090.99.0020	23039383

##### Documents

01.02.0777	security instruction
01.02.1507	mounting instruction

**HUBER+SUHNER group is certified according to ISO 9001 and ISO 14001.**

##### WAIVER!

While the information contained has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG  
Mobile Communications + Electronics Sector  
Communication Equipment Components  
CH-9100 Herisau, Switzerland  
Tel.: +41 (0)71 353 41 11  
Fax: +41 (0)71 353 47 51  
www.hubersuhner.com

Document no.: 01.02.0907  
Issue no.: 6  
Supersedes: 10.2004

##### Uncontrolled Copy

Issued/Checked/Released: 4159/4417/10.2004  
Last amended: 4159