DATA SHEET

Transceivers
1G SFP Copper
CSE-300A99

Properties

- Protocol 1G Ethernet
- Data rate 1000 Mbps
- Reach up to 100m
- Rx LOS implemented
- RJ45 connector
- CAT7 cable
- Temp. range 0 ... 70°C
- SERDES interface



General data	
Form factor	SFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	1G Ethernet
Data rate standards	1000BASE-T
Media type	Copper
Connector	RJ 45
Built-in FEC	No
Mechanical Standard	SFF-8431
Management Interface	SFF-8472
Electrical Interface	SERDES
Auto Negotiation	No
CDR	none
Operation temperature	0 °C ... 70 °C
Supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 375 mA
Power consumption	< 1.2 W
Digital Diagnostic Management (DDM)	No

Absolute Maximum Ratings	
Max. supply voltage range	-0.3 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 85 %

Receiver Specifications	
Receiver LOS Link Indication	Implemented

Transceivers
1G SFP Copper
CSE-300A99

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CSE-300A99xxxx-99	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-99: N/A

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P28433 / Date of publication: 02.11.2026 / uncontrolled copy