DATA SHEET

Transceivers
1G SFP CWDM EZX
CSS-332A34

Properties

- Multi-protocol support
- Data rate 125 Mbps and 1.0625...1.25 Gbps
- Reach up to 160km
- Any ITU CWDM channel between 1471nm and 1611nm
- LC/PC duplex connector
- Singlemode fiber
- Temp. range 0 ... 70°C
- Link budget at least 34 dB
- Power consumption < 1 W



General data	
Form factor	SFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	1G Ethernet, 1G Fiber Channel, CPRI 2
Data rate standards	1000BASE-EZX
	CPRI Option 2
Media type	Singlemode
Connector	LC/PC duplex
Modulation Format	NRZ
Built-in FEC	No
CDR	none
Operation temperature	0 °C ... 70 °C
Supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 300 mA
Power consumption	< 1 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 95 %

Transceivers

1G SFP CWDM EZX

CSS-332A34

Transmitter Specifications	
Laser Type	Uncooled DFB
Grid	CWDM 20nm
Available Wavelength in nm	Any ITU CWDM channel between 1471nm and 1611nm
Average launch power per lane	1 dBm ... 6 dBm
Extinction Ratio	> 9 dB
Side Mode Suppression	> 30 dB
Supported Data rate	125 Mbps / 1.0625 Gbps ... 1.25 Gbps

Receiver Specifications	
Receiver Type	APD
Operating Wavelength Range	1260 nm ... 1620nm
Receiver Overload	> -10 dBm
Receiver Sensitivity	< -33 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -36 dBm
Receiver LOS Assert	> -42 dBm
Receiver LOS Hysteresis	> 0.5 dB
Supported Data rate	125 Mbps / 1.0625 Gbps ... 1.25 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CSS-332A34xxxx-ww	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-ww: CWDM channel chosen from table at the end

Channel Allocation			
Code	Wavelength (nm)	Code	Wavelength (nm)
-47	1471	-55	1551
-49	1491	-57	1571
-51	1511	-59	1591
-53	1531	-61	1611

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P28451 / Date of publication: 02.11.2026 / uncontrolled copy