DATA SHEET

Transceivers
2.5G SFP ZX
CSS-630A28

Properties

- Multi-protocol support
- Data rate 125 Mbps...2.67 Gbps
- Reach up to 80km
- Wavelength 1550nm
- LC/PC duplex connector
- Singlemode fiber
- Temp. range -40 ... 85°C
- Link budget at least 28 dB
- Power consumption < 1 W



General data	
Form factor	SFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	STM-16/4/1, 1G Ethernet, CPRI Option 1...3
Data rate standards	SDH STM-16/4/1
	1000BASE-ZX
	CPRI Option 1 ... 3
Media type	Singlemode
Connector	LC/PC duplex
Modulation Format	NRZ
Built-in FEC	No
CDR	none
Operation temperature	-40 °C ... 85 °C
Supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 300 mA
Power consumption	< 1 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 95 %

HUBER+SUHNER

Transceivers

2.5G SFP ZX

CSS-630A28

Transmitter Specifications	
Laser Type	Uncooled DFB
Operating Wavelength Range	1530 nm ... 1570nm
Grid	None
Average launch power per lane	0 dBm ... 5 dBm
Extinction Ratio	> 8.2 dB
Side Mode Suppression	> 30 dB
Supported Data rate	125 Mbps ... 2.67 Gbps

Receiver Specifications	
Receiver Type	APD
Operating Wavelength Range	1260 nm ... 1620nm
Receiver Overload	> -9 dBm
Receiver Sensitivity	< -28 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -28 dBm
Receiver LOS Assert	> -38 dBm
Receiver LOS Hysteresis	> 0.5 dB
Supported Data rate	125 Mbps ... 2.67 Gbps
Maximum Receiver Power (Damage Threshold)	> -9 dBm

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CSS-630A28xxxx-15	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-15: 1550nm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P30276 / Date of publication: 03.11.2026 / uncontrolled copy