DATA SHEET

Transceivers
10G XFP Bidi LR
CXB-700A08

Properties

- Multi-protocol support
- Data rate 9.95...11.3 Gbps
- Reach up to 10km
- Wavelength 1270/1330 or 1330/1270nm
- LC/PC simplex connector
- Singlemode fiber
- Temp. range 0 ... 70°C
- Link budget at least 8 dB



General data	
Form factor	XFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	10G Ethernet LAN/WAN, 10G FC, STM-64, OTN-2
Data rate standards	10GBASE-LR/LW
Media type	Singlemode
Connector	LC/PC simplex
Modulation Format	NRZ
Built-in FEC	No
CDR	Double
Operation temperature	0 °C ... 70 °C
Supply voltage typical	3.13 V ... 3.47 V
Power consumption	< 2 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 85 %

Transmitter Specifications	
Laser Type	Uncooled DFB
Operating channels	1270nm (1260.00 to 1280.00nm) 1330nm (1320.00 to 1340.00nm)
Grid	None
Available Wavelength in nm	Tx 1270nm/Rx 1330nm Tx 1330nm/Rx 1270nm
Average launch power per lane	-5 dBm ... 0 dBm

Transceivers

10G XFP Bidi LR

CXB-700A08

Transmitter Specifications	
Extinction Ratio	> 3.5 dB
Side Mode Suppression	> 30 dB
Supported Data rate	9.95 Gbps ... 11.3 Gbps

Receiver Specifications	
Receiver Type	PIN
Operating channels	1270nm (1260.00 to 1280.00nm)
	1330nm (1320.00 to 1340.00nm)
Receiver Overload	> -0.5 dBm
Receiver Sensitivity	< -15 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -18 dBm
Receiver LOS Assert	> -32 dBm
Receiver LOS Hysteresis	> 0.5 dB
Supported Data rate	9.95 Gbps ... 11.3 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CXB-700A08xxxx-ww	"xxxx" is an alphanumerical string, describing the compatibility. "0000" means no special coding to ensure compatibility with a special switch type.	-23: 1270nm Laser / 1330nm Receiver
		-32: 1330nm Laser / 1270nm Receiver

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P30283 / Date of publication: 11.11.2026 / uncontrolled copy