DATA SHEET

Transceivers
10G XFP ZR+
CXS-722A26

Properties

- Multi-protocol support
- Data rate 9.95...11.3 Gbps
- Reach up to 100km
- Wavelength 1550nm
- LC/PC duplex connector
- Singlemode fiber
- Temp. range 0 ... 70°C
- Link budget at least 26 dB (w/o dispersion penalty)



General data	
Form factor	XFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	10G Ethernet LAN/WAN, 10G FC, STM-64, OTN-2
Data rate standards	10GBASE-ZR/ZW
Media type	Singlemode
Connector	LC/PC duplex
Modulation Format	NRZ
Built-in FEC	No
CDR	Double
Operation temperature	0 °C ... 70 °C
Supply voltage typical	4.75 V ... 5.25 V
Additional supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 350 mA
Additional supply current	< 450 mA
Power consumption	< 3.5 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 6 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 85 %

Transmitter Specifications	
Laser Type	EML
Operating Wavelength Range	1530 nm ... 1570nm
Grid	None

Transceivers

10G XFP ZR+

CXS-722A26

Transmitter Specifications	
Average launch power per lane	1 dBm ... 5 dBm
Dispersion Penalty	< 3 dB
Extinction Ratio	> 9 dB
Side Mode Suppression	> 30 dB
Supported Data rate	9.95 Gbps ... 11.3 Gbps

Receiver Specifications	
Receiver Type	APD
Operating Wavelength Range	1260 nm ... 1620nm
Receiver Overload	> -6 dBm
Receiver Sensitivity	< -25 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -27 dBm
Receiver LOS Assert	> -37 dBm
Receiver LOS Hysteresis	> 0.5
Supported Data rate	9.95 Gbps ... 11.3 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CXS-722A26xxxx-15	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-15: 1550nm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P30295 / Date of publication: 11.11.2026 / uncontrolled copy