DATA SHEET

Transceivers
8G XFP LR
CXS-802A09

Properties

- Multi-protocol support
- Data Rate 2.125...8.5 Gbps
- Reach up to 10km
- Wavelength 1310nm
- LC/PC duplex connector
- Singlemode fiber
- Temp. range 0 ... 70°C
- Link budget at least 9 dB



General data	
Form factor	XFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	2/4/8G Fiber Channel
Data rate standards	FC-PI-4 800-SM-LL-L
Modulation Format	NRZ
Built-in FEC	No
CDR	Double
Operation temperature	0 °C ... 70 °C
Supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 600 mA
Power consumption	< 2 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 85 %

Transmitter Specifications	
Laser Type	Uncooled DFB
Operating Wavelength Range	1290 nm ... 1330nm
Grid	None
Average launch power per lane	-6 dBm ... -1 dBm
Extinction Ratio	> 3.5 dB
Side Mode Suppression	> 30 dB
Supported Data rate	2.125 Gbps ... 8.5 Gbps

Transceivers

8G XFP LR

CXS-802A09

Receiver Specifications	
Receiver Type	PIN
Operating Wavelength Range	1260 nm ... 1620nm
Receiver Overload	> -0.5 dBm
Receiver Sensitivity	< -15 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -18 dBm
Receiver LOS Assert	> -32 dBm
Receiver LOS Hysteresis	> 0.5 dB
Supported Data rate	2.125 Gbps ... 8.5 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CXS-802A09Dxxxx-13	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-13: 1310nm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P30301 / Date of publication: 11.11.2026 / uncontrolled copy