DATA SHEET

Transceivers
1G SFP SX
CSM-301A08

Properties

- Multi-protocol support
- Data rate 125 Mbps and 1.0625...1.25 Gbps
- Reach up to 550m
- Wavelength 850nm
- LC/PC duplex connector
- Multimode fiber
- Temp. range -40 ... 85°C
- Link budget at least 8 dB
- Power consumption < 1 W



General data	
Form factor	SFP
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	1G Ethernet, 1G Fiber Channel, CPRI 2
Data rate standards	1000BASE-SX
	CPRI Option 2
Media type	Multimode
Connector	LC/PC duplex
Modulation Format	NRZ
Built-in FEC	No
CDR	none
Operation temperature	-40 °C ... 85 °C
Supply voltage typical	3.13 V ... 3.47 V
Supply Current	< 280 mA
Power consumption	< 1 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.5 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 95 %

Transmitter Specifications	
Laser Type	VCSEL
Operating Wavelength Range	830 nm ... 860nm
Grid	None

HUBER+SUHNER

Transceivers

1G SFP SX

CSM-301A08

Transmitter Specifications	
Average launch power per lane	-9 dBm ... -3 dBm
Extinction Ratio	> 9
Side Mode Suppression	> 30 dB
Supported Data rate	125 Mbps / 1.0625 Gbps ... 1.25 Gbps

Receiver Specifications	
Receiver Type	PIN
Operating Wavelength Range	770 nm ... 860nm
Receiver Overload	> 0 dBm
Receiver Sensitivity	< -17 dBm
Bit Error Rate at Receiver	1E-12
Receiver LOS De-Assert	< -18 dBm
Receiver LOS Assert	> -35 dBm
Receiver LOS Hysteresis	> 0.5
Supported Data rate	125 Mbps / 1.0625 Gbps ... 1.25 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CSM-301A08xxxx-85	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-85: 850nm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P30243 / Date of publication: 02.11.2026 / uncontrolled copy