DATA SHEET


Power cable

2 core Power Cable, 12 AWG, braided copper shielding

02-12AWG-05-PVC-10-UL-TC

Properties

- DC Power copper cable for supply of RRH
- Suitable for outdoor environment
- Braided copper shielding
- Voltage rating 600 V
- UL listed Tray Cable TC



Conductor		
General	Number of conductors	2 pcs
	Cross section	10 AWG
Insulation	Material	PVC/Nylon
	Diameter	3.4 mm
Conductor electrical values	Resistance of core	1.65 Ω/kft
	Resistance of core temperature	20 °C
	Current rating	30 A
	Operating voltage	0.6 kV AC / 1kV DC
	Test voltage	8.4 kV DC
	Test voltage duration	5 min

Cable jacket		
Outer jacket	Material	PVC
	Diameter	10.3 mm
	Thickness	1.14 mm

Ordering Information Table	
Item number	Item description
85020805	02-12AWG-05-PVC-10-UL-TC

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P17518 / Date of publication: 26.09.2023 / uncontrolled copy