
DATA SHEET

Power cables
2 core Power Cable, 6 mm2, Class 5, Dca
02-06mm2CL5-S05-LSFH14BK-CE#D

Properties

- Flexible power cable with low bending radius and excellent cable routing properties
- Braided copper shielding
- Low smoke free of halogen thermoplastic jacket material



General data	
Cable media type	Power cables
Weight per length	approx. 310 g/m

Conductor		
General	Number of conductors	2 pcs
	Cross section	6 mm²
Conductor class	Conductor class standard	IEC 60228
	Conductor class	Class 2
Insulation	Material	XLPE
	Diameter	4.2 mm
	Marking / colour coding	Blue / Brown
Conductor electrical values	Resistance of core	3.3 Ω/km
	Resistance of core temperature	20 °C
	Current rating	45 A
	Operating voltage	0.6 kV AC / 1kV DC
	Test voltage	8.4 V DC
	Test voltage duration	5 min

Cable screen	
Material	Copper
Type	braiding
Coverage	80 %

Cable jacket		
Outer jacket	Material	LSFH TM thermoplastic TPE-HF
	Diameter	13.7 mm
	Thickness	1.8 mm
	CPR standard	EN 50575:2014+A1:2016

Power cables

2 core Power Cable, 6 mm2, Class 5, Dca

02-06mm2CL5-S05-LSFH14BK-CE#D

Cable jacket		
	CPR class	Dca-s2,d2,a1

Ordering Information Table	
Item number	Item description
85138936	02-06mm2CL5-S05-LSFH14BK-CE#D

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P17513 / Date of publication: 25.04.2024 / uncontrolled copy