DATA SHEET

Fiber Optic Cables
Simplex 0.9mm Tight Tube TPU Ø 1.9mm
01-.../FJZ-...19

Properties

- Metal free indoor and outdoor cable
- Each fiber strain relieved
- Tube can be stripped up to 30mm in one piece
- Tight bending radii
- For high mechanical and thermal stability
- Halogen free and non-corrosive fire gases



Jacket colour



Construction		
Fiber	Quantity: up to	1
	Type	coloured
Tube	Quantity	1 pcs
	Diameter	0.9 mm
Strain relief	Type	aramide yarn
Outer jacket	Material	TPU
	Diameter	1.9mm

Environmental data		
Temperature	Standard	IEC 61300-2-22
	During installation	-10 °C ... 50 °C
	In service	-40 °C ... 85 °C
	In storage	-40 °C ... 85 °C

Mechanical data		
Weight		approx. 3 g/m
Tensile strength	Standard	IEC 60794-1-2 E1
	During installation	180 N
	In service	90 N
Min. bending radius	Standard	IEC 60794-1-2 E11
	During installation	50 mm
	In service	25 mm
Repeated bending	Standard	IEC 60794-1-2 E6
	Radius	30 mm
	Weight	1 kg
	Cycles	2500

Fiber Optic Cables

Simplex 0.9mm Tight Tube TPU Ø 1.9mm

01-.../FJZ-...19

Mechanical data		
Crush resistance	Standard During installation In service	IEC 60794-1-2 E3 10000 N/dm 2000 N/dm
Impact resistance	Standard Energy Cycles	IEC 60794-1-2 E4 0.74 J 30

Colours	
Fiber	According to colour code
Tube	E9: YE, G50: OG, G62: BU, OM3: TQ, OM4: HV
Standard outer jacket colours	Yellow
	Orange
	Turquoise
	Heather violet
	Black
	Green

Type of fiber	
Fiber type	**Fiber standard**
E9/125	according to IEC 60793-2-50 B-652.D + ITU-T G.652.D
G62,5/125-OM1	according to IEC 60793-2-10 A1-OM1
G50/125-OM2	according to IEC 60793-2-10 A1-OM2b + ITU-T G.651.1
G50/125-OM3	according to IEC 60793-2-10 A1-OM3b
G50/125-OM4	according to IEC 60793-2-10 A1-OM4b
E9/125A2	according to IEC 60793-2-50 B-657.A2 + ITU-T G.657.A2
E9/125A3	according to IEC 60793-2-50 B-657.B3 + ITU-T G.657.B3

Fiber colour code

	1	2	3	4	5	6	7	8	9	10	11	12
H+S Standard	Red	Green	Yellow	Blue	White	Violet	Orange	Black	Grey	Brown	Heather violet	Turquoise
DIN	Red	Green	Blue	Yellow	White	Grey	Brown	Violet	Turquoise	Black	Orange	Heather violet
TIA	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Violet	Heather violet	Turquoise
IEC	Blue	Yellow	Red	White	Green	Violet	Orange	Grey	Turquoise	Black	Brown	Heather violet

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P7400 / Date of publication: 13.05.2026 / uncontrolled copy