DATA SHEET

Fiber Optic Cables

Empty Tube Simplex TPU Ø 1.9mm-0.4mm

00-0/CHJZ-...19

Properties

- Metal free indoor and outdoor cable
- Strain relieved with aramide yarn



Jacket colour

Construction		
Tube	Diameter	0.94 mm
Strain relief	Type	aramide yarn
Outer jacket	Material	TPU
	Diameter	1.9mm

Environmental data		
Temperature	Standard	IEC 61300-2-22
	During installation	-10 °C ... 50 °C
	In service	-40 °C ... 85 °C
	In storage	-40 °C ... 85 °C

Mechanical data		
Weight		approx. 2.7 g/m
Tensile strength	Standard	IEC 60794-1-2 E1
	During installation	100 N
	In service	50 N
Min. bending radius	Standard	IEC 60794-1-2 E11
	During installation	25 mm
	In service	25 mm
Crush resistance	Standard During installation In service	IEC 60794-1-2 E3 1000 N/dm 500 N/dm
Impact resistance	Standard Energy Cycles	IEC 60794-1-2 E4 0.74 J 20

Fiber Optic Cables

Empty Tube Simplex TPU Ø 1.9mm-0.4mm

00-0/CHJZ-...19

Colours	
Tube	White or natural
Standard outer jacket colours	Orange
	Red
	Heather violet
	Lime-Green
	Black
	Turquoise
	Yellow

Fiber colour code

	1	2	3	4	5	6	7	8	9	10	11	12
H+S Standard	Red	Green	Yellow	Blue	White	Violet	Orange	Black	Grey	Brown	Heather violet	Turquoise
DIN	Red	Green	Blue	Yellow	White	Grey	Brown	Violet	Turquoise	Black	Orange	Heather violet
TIA	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Violet	Heather violet	Turquoise
IEC	Blue	Yellow	Red	White	Green	Violet	Orange	Grey	Turquoise	Black	Brown	Heather violet

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P7422 / Date of publication: 13.05.2026 / uncontrolled copy