DATA SHEET

Transceivers
25G SFP28 LR
CSS-443A06

Properties

- Multi-protocol support
- Data rate 9.83...11.3 / 24.33...25.78 Gbps
- Reach up to 20km
- Wavelength 1310nm
- LC/PC duplex connector
- Singlemode fiber
- Temp. range -40 ... 85°C
- Link budget at least 6 dB



General data	
Form factor	SFP28
Product image	Actual product may differ from the images shown. Colours, design, and details can vary.
Protocol	10/25G Ethernet, eCPRI, CPRI 7/8/10
Data rate standards	25GBASE-LR
	25G eCPRI
	CPRI Option 7,8,10
Media type	Singlemode
Connector	LC/PC duplex
Modulation Format	NRZ
Built-in FEC	No
CDR	Double, with bypass control (by HW pins or RS bits)
Operation temperature	-40 °C ... 85 °C
Supply voltage typical	3.13 V ... 3.47 V
Power consumption	< 1.2 W
Digital Diagnostic Management (DDM)	Yes
Laser hazard level	1

Absolute Maximum Ratings	
Max. supply voltage range	-0.3 V ... 4 V
Max. Storage Temperature Range	-40 °C ... 85 °C
Max. relative humidity range	5 % ... 95 %

Transmitter Specifications	
Laser Type	Uncooled DFB
Operating Wavelength Range	1260 nm ... 1355nm
Grid	None
Average launch power per lane	-5 dBm ... 2 dBm

Transceivers

25G SFP28 LR

CSS-443A06

Transmitter Specifications	
Side Mode Suppression	> 30 dB
Supported Data rate	9.83 Gbps ... 11.3 Gbps / 24.33 Gbps ... 25.78 Gbps

Receiver Specifications	
Receiver Type	PIN
Operating Wavelength Range	1260 nm ... 1620nm
Receiver Overload	> 2 dBm
Receiver Sensitivity	< -10.6 dBm
Bit Error Rate at Receiver	5E-5
Maximum Optical Input Power per Lane (Overload)	3 dBm
Receiver LOS De-Assert	< -13 dBm
Receiver LOS Assert	> -30 dBm
Receiver LOS Hysteresis	> 0.5 dB
Supported Data rate	9.83 Gbps ... 11.3 Gbps / 24.33 Gbps ... 25.78 Gbps

Ordering Information Table		
Order Code	Compatibility code explanation	Wavelength code explanation
CSS-443A06xxxx-13	“xxxx” is an alphanumerical string, describing the compatibility. “0000” means no special coding to ensure compatibility with a special switch type.	-13: 1310nm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P39107 / Date of publication: 26.10.2026 / uncontrolled copy