DATA SHEET

Multicoax breakout, 2x8, MXPM (male) to PC185 (female), 50 Ohm, 70 GHz, 152mm

MF53/2x8A_11MXPM/21PC185_e/152

Properties

- Operating range at up to 70 GHz
- Broadband characteristic
- Standard absolute phase matching down to ± 1 ps
- Highly flexible and ultra stable Multiflex cable
- 2.54 mm (0.1 inch) pitch centre-to-centre
- Magnetic locking mechanism
- Automatic interface protection
- Cost efficient PCB sockets



Product configuration	
MULTICOAX assembly type	Breakout
Type of cable	MULTIFLEX_53-02
Type description connector A	2x8A_11_MXPM
Type description connector B	21_PC185
Length	152 mm
Length	6 inch
Length type	REF to REF

Electrical data	
Impedance	50 Ω
Max. operating frequency	70 GHz

Environmental data	
Operation temperature	0 °C ... 85 °C

Ordering information	
Item number	Item description
85096261	MF53/2x8A_11MXPM/21PC185_e/152

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

Multicoax breakout, 2x8, MXPM (male) to PC185 (female), 50 Ohm, 70 GHz, 152mm
MF53/2x8A_11MXPM/21PC185_e/152

DOCUMENT PIM-P38247 / Date of publication: 09.09.2024 / uncontrolled copy