

## Copper Patch Panel

Category 6A cassette for 24 pairs cable

### Description

This cassette module suit for Category 6A / Class EA applications in accordance with ISO/IEC 11801, TIA/EIA 568-C.2

- 1 Cassette module presents 6 RJ-45 ports at front and 1 trunk terminal block at rear.
- Compatible with Cassette patch panel
- Housing made of Zinc-alloy fully shielded
- Contact spring with phosphor bronze alloy, plated with gold.
- IDC made of phosphor bronze alloy.
- Suitable for PoE/PoE+ application



### Technical data

#### Construction

Description	Values	Comment
Dimension (W x H x D)	92.95 x 18 x 90mm	
Colour	Silver	
Main construction	Metal	

#### Mechanical and environmental data

Characteristics	Values	Tested acc. to	Comment
For solid copper wire	AWG 22 -AWG 24		
For strand copper wire	AWG 26/7 strand		
Insertion/extraction life	750 cycles minimum		
Rear cable access diameter	14.5~18.5 mm		
Compliant with RoHS and REACH	Yes		

#### Electrical data

Description	Values	Comment
Insulation resistance	500 MΩ min. @100V d.c	
Dielectric withstanding voltage:	1000V d.c. or a.c. peak contact to contact @60Hz for 1 minute.	

### Ordering information

Description	Item number	Comment
Category 6A multi jack cassette module snap-in FTP, ½ U 6 ports, for 24 pairs cable, Silver	85075740	

### Related documents

Description	Document number
User manual for installation	DOC-0000750646

### Additional information

Description	
Microsite for Data Center solution	<a href="http://datacenter.hubersuhner.com">datacenter.hubersuhner.com</a>