

Product Positioning: DEFENCE VEHICLES



Product	VOP	Attenuation	Frequency Range min. <small>(of product family)</small>	Frequency Range max. <small>(of product family)</small>	RF Leakage	Space saving	MIL Assembly Qualification	MIL-DTL-17 Cable Qualification	Water tightness IP68	Dynamic application <small>(multiply bendable)</small>	Flex-Life	Halogenfree Dielectric	Halogenfree Jacket	Field mountable	Armouring	MULTIPOINT compatibility	Price Level	Available as bulk
Semi Rigid	71%	✓	18	67	✓✓✓	✓✓	No	Available	Yes	No	n/a	No	n/a	No	No	No	\$\$	Yes
SUCOFORM	71%	✓	18	67	✓✓✓	✓✓	No	No	No	No	n/a	No	Available	No	No	No	\$	Yes
MULTIFLEX	71%	✓	33	67	✓✓	✓	No	No	No	Yes	✓	No	Available	No	No	Yes	\$\$	Yes
Minibend/Microbend	71%	✓✓	67	90	✓✓	✓✓✓	Yes	Yes	Yes (W+WR)	Yes	✓	No	No	No	No	No	\$\$\$	no
Minibend-L/Mini 141	76%	✓✓✓	40	50	✓✓	✓✓✓	Yes	Yes	Yes (W+WR)	Yes	✓	No	No	No	No	No	\$\$\$	no
everflex	76%	✓✓	12	40	✓✓	✓✓	No	No	No	Yes	✓✓✓✓	No	Yes	No	No	No	\$\$\$\$	no
SPUMA	85%	✓✓✓✓	6	6	✓✓	✓	No	No	No	Yes	✓	Yes	Yes	No	No	No	\$	Yes
ENVIROFLEX	71%	✓	6	6	✓	✓	No	No	No	Yes	✓	Yes	Yes	No	No	No	\$	Yes
RG	71%	✓	6	6	✓	✓	No	Yes	No	Yes	✓	No	No	No	No	No	\$	Yes
SUCOFEEED	88%	✓✓✓✓	3	3	✓✓✓	✓	No	No	Yes	No	n/a	Yes	Yes	No	No	No	\$	Yes
SUCOFLEX 100	76%	✓✓✓	18	50	✓✓	✓	Yes	No	Yes	Yes	✓	No	Available	No	on request	Yes	\$\$\$\$	no
SUCOFLEX 100 P	76%	✓✓✓	18	50	✓✓	✓	Yes	No	Yes	Yes	✓✓	No	Available	No	on request	Yes	\$\$\$\$	no
EACON	76%	✓✓✓	6	18	✓✓	✓	No	No	Yes	Yes	✓	No	Available	Yes	on request	No	\$\$\$\$	Yes
Astro-steel-flex I	70%	✓	18	34	✓	✓	No	Yes	Yes	Yes	✓	No	No	No	on request	No	\$\$\$	Yes
Astro-steel-flex II	76%	✓✓✓	18	40	✓	✓	No	Yes	Yes	Yes	✓	No	No	No	on request	No	\$\$\$	Yes
Astro-boa-flex I	77%	✓✓✓	18	26	✓	✓	No	No	Yes	Yes	✓	No	No	No	on request	No	\$\$\$	Yes
Astro-boa-flex II	78%	✓✓✓	14	14	✓	✓	No	No	Yes	Yes	✓	No	No	No	on request	No	\$\$\$\$	Yes
32061 (110 GHz)	71%	✓	110	110	✓✓	✓✓	No	No	Yes	Yes	✓	No	No	No	No	No	\$\$\$\$	no