


Data Sheet

SUCOFLEX_Stock Assembly

Description

The SUCOFLEX 104 high end cable assemblies are designed to provide optimal performance up to 26.5 GHz where stringent electrical requirements – in particular stability and low loss, are important.

Product description SF104/PC35m/PC35m/500mm
Item number 84017154



Product Configuration

Cable type	SUCOFLEX_104
Length of assembly	500 mm
Connector A	PC3.5 straight male
Connector B	PC3.5 straight male

Technical Data

Mechanical Data

Diameter:	5.5 mm
Min. bending radius static	16 mm
Min. bending radius repeated	25 mm
Recommended mating torque (*)	0.8... 1.1 Nm
Weight	50 g

Environmental Data

Operating temperature	- 55°C to + 90°C
Storage temperature	- 40°C to + 85°C
RoHS, REACH	Compliant

Electrical Data

Impedance	50 Ω
Operating frequency	up to 26.5 GHz
Velocity of propagation	77 %
Capacitance	87 pF / m
Time delay	4.3 ns / m

Return Loss	min. 16.6 dB	(up to 26.5 GHz)
Insertion loss (assembly)	max. 1.01 dB	(26.5 GHz, 25°C)
Power handling	min. 200 W	(26.5 GHz, sea level, 25°C)
Screening effectiveness	> 90 dB	(up to 18 GHz)
Insertion loss stability vs. bending (**)	+/- 0.2 dB	(up to 26.5 GHz)
Phase stability vs. bending (**)	< 1.7°	(el/GHz)

General Information

(*) H+S torque wrench H+S description: 74_Z-0-0-21 // material/item number: 22543130
 (**) Stability test 360°, diameter 55 mm