

RADOX EN 50306-4 3P 300V MM S

Construction n x mm ²	Conductor nom. Dia mm	Core Dia. nom. mm	Screen Dia. mm	Cable dia. mm	R ₂₀ ²⁾ max. Ω/km	Fireload nom. kJ/m	Combustible material nom. kg/100m	Cable Weight nom. kg/100m	H + S Part No.
2x0.5	0.9	1.42	3.3	4.9±0.2	40.1	325	2.4	4.0	12586036
3x0.5	0.9	1.42	3.5	5.0±0.2	40.1	335	2.4	4.5	12586037
4x0.5	0.9	1.42	3.9	5.4±0.2	40.1	380	2.7	5.4	12586038
6x0.5	0.9	1.42	5.0	6.3±0.2	40.1	560	3.5	7.5	12586039
8x0.5	0.9	1.42	5.6	6.7±0.3	40.1	610	3.8	8.8	12586040
9x0.5	0.9	1.42	6.6	8.0±0.3	40.1	920	5.8	12.0	85087574
10x0.5	0.9	1.42	6.3	7.9±0.3	40.1	820	5.2	11.8	84101234
12x0.5	0.9	1.42	6.5	8.2±0.3	40.1	990	5.4	13.0	84101235
15x0.5	0.9	1.42	7.4	9.0±0.3	40.1	1090	6.3	16.4	12586100
16x0.5	0.9	1.42	7.4	9.0±0.3	40.1	1090	6.4	16.1	84110710
2x0.75	1.1	1.62	3.7	5.1±0.3	26.7	345	2.6	4.7	12586041
3x0.75	1.1	1.62	4.0	5.4±0.3	26.7	370	2.6	5.6	12586042
3G0.75	1.1	1.62	4.0	5.4±0.3	26.7	370	2.6	5.6	84122834
4x0.75	1.1	1.62	4.6	5.9±0.3	26.7	470	3.1	7.0	12586043
6x0.75	1.1	1.62	5.7	6.8±0.3	26.7	640	4.0	9.6	12586044
8x0.75	1.1	1.62	6.1	7.4±0.2	26.7	705	4.3	11.9	12586045
12x0.75	1.1	1.62	7.4	9.2±0.3	26.7	1110	6.9	17.6	84134205
2x1	1.2	1.77	4.0	5.4±0.2	20.0	375	2.8	5.4	12586046
3x1	1.2	1.77	4.4	5.8±0.2	20.0	445	3.1	6.8	12586047
4x1	1.2	1.77	5.1	6.3±0.2	20.0	500	3.3	8.5	12586048
6x1	1.2	1.77	6.0	7.3±0.3	20.0	705	4.4	11.6	12586049
8x1	1.2	1.77	6.7	8.3±0.3	20.0	870	5.5	14.8	12586050
10x1	1.2	1.77	7.8	9.5±0.4	20.0	1070	6.7	18.9	84094674
2x1.5	1.5	2.17	4.8	6.4±0.3	13.7	545	4.0	7.6	12586051
3x1.5	1.5	2.17	5.3	6.7±0.3	13.7	595	4.0	9.0	12586052
4x1.5	1.5	2.17	5.8	7.3±0.3	13.7	650	4.5	11.4	12586053
4G1.5	1.5	2.17	5.8	7.3±0.3	13.7	650	4.5	11.4	84135186
6x1.5	1.5	2.17	7.2	8.9±0.3	13.7	1070	6.7	16.9	12586054
8x1.5	1.5	2.17	8.1	9.8±0.3	13.7	1180	7.4	21.1	12586055
12x1.5	1.5	2.17	10.0	11.9±0.4	13.7	1680	10.3	31.6	84134204

2x2.5	1.9	2.75	6.1	7.9±0.3	8.21	830	5.7	11.9	12586056
3x2.5	1.9	2.75	6.6	8.25±0.3	8.21	875	5.8	14.4	12586057
4x2.5	1.9	2.75	7.5	9.3±0.3	8.21	1110	7.3	18.3	12586058
5x2.5	1.9	2.75	8.5	10.2±0.4	8.21	1330	8.4	22.6	84115627
6x2.5	1.9	2.75	9.2	10.9±0.4	8.21	1550	9.6	26.4	84094675
7x2.5	1.9	2.75	8.8	10.8±0.4	8.21	1405	9.2	27.4	84115630

Cables with coloured cores:

Construction n x mm ²	Conductor nom. Dia mm	Core Dia. nom. mm	Screen Dia. mm	Cable dia. mm	R ₂₀ ²⁾ max. Ω/km	Fireload nom. kJ/m	Combustible material nom. kg/100m	Cable Weight nom. kg/100m	H + S Part No.	Core Colours
4 V 0.5	0.9	1.42	3.9	5.4±0.2	40.1	380	2.7	5.4	85067099	YE GN BN WH