

RADOX EN 50306-4 7E 300V MM S

Construction n x mm ²	Conductor nom. Dia mm	Core Dia. nom. mm	Screen Dia. mm	Cable dia. mm	R ₂₀ ²⁾ max. Ω/km	Fireload nom. kJ/m	Combustible material nom. kg/100m	Cable Weight nom. kg/100m	H + S Part No.
2 x 2 x 0.5	0.9	1.42	6.0	8.4±0.3	40.1	910	6.9	10.4	85084449
3 x 2 x 0.5	0.9	1.42	6.2	8.65±0.3	40.1	920	6.9	11.3	85084450
4 x 2 x 0.5	0.9	1.42	6.8	9.25±0.3	40.1	985	7.1	13.1	85084451
6 x 2 x 0.5	0.9	1.42	8.8	11.4±0.4	40.1	1640	11.4	19.6	85109559
7 x 2 x 0.5	0.9	1.42	8.2	10.8±0.4	40.1	1315	9.1	17.7	85157676
2 x 2 x 0.75	1.0	1.62	6.7	9.1±0.3	26.7	1050	7.8	12.5	85084452
3 x 2 x 0.75	1.0	1.62	7.3	9.7±0.3	26.7	1105	8.1	14.6	85109560
4 x 2 x 0.75	1.0	1.62	7.8	10.3±0.4	26.7	1240	9.0	16.4	85157677
7 x 2 x 0.75	1.0	1.62	9.6	12.1±0.4	26.7	1555	10.9	23.5	85157678
2 x 2 x 1.0	1.2	1.77	7.2	9.65±0.3	20.0	1120	8.4	14.6	85084453
3 x 2 x 1.0	1.2	1.77	7.7	10.3±0.4	20.0	1230	9.0	16.8	85084454
4 x 2 x 1.0	1.2	1.77	8.3	10.9±0.4	20.0	1330	9.7	19.3	85084455
7 x 2 x 1.0	1.2	1.77	10.3	12.9±0.4	20.0	1660	11.6	28.2	85109561
2 x 2 x 1.5	1.5	2.17	8.6	11.1±0.4	13.7	1585	11.1	18.9	85109562
3 x 2 x 1.5	1.5	2.17	9.3	11.9±0.4	13.7	1660	11.8	22.1	85157679
4 x 2 x 1.5	1.5	2.17	10.2	12.7±0.4	13.7	1765	12.2	25.9	85157680
7 x 2 x 1.5	1.5	2.17	13.2	15.8±0.5	13.7	2585	17.8	42.6	85142315