

SENCITY® SC Omni-M 1399.99.0338

Description

Rugged omni-directional antenna for installation on outdoor cabinets.
 Supports TETRA, LTE450, 2G/3G/4G/5G cellular, Wifi 2.4/5 GHz, Wifi 6E and GNSS (Beidou, Galileo, GPS, Glonass).
 3 separate ports for 2x TETRA/cellular plus GNSS.
 Meets ETSI 300 019-1-4 class 4.1E.
 Low profile housing.
 Single hole mounting, easy cabling feed-through.



Product Configuration

Technical Data

Electrical Data

| | Band 1 | Band 2 | Band 3 | Band 4 |
|--------------------------|--------------|-----------|-------------|-------------|
| Band Name | TETRA/LTE450 | Cellular | Cellular | Cellular |
| Frequency (MHz) | 380 - 470 | 694 - 960 | 1350 - 2700 | 3300 - 4200 |
| VSWR | 2.5 | 2.0 | 2.0 | 2.0 |
| Impedance (Ohm) | 50 | 50 | 50 | 50 |
| Gain (dBi) | 3 | 2 | 4 | 4 |
| Composite power max (W) | 40 | 40 | 40 | 40 |
| Ambient temperature (°C) | 25 | 25 | 25 | 25 |
| Port isolation (dB) | 3 | 8 | 15 | 20 |

| | Band 5 | Band 6 | Band 7 | Band 8 |
|--------------------------|-------------|-------------|-------------|-------------|
| Band Name | Cellular | WiFi | WiFi | GNSS |
| Frequency (MHz) | 4900 - 7125 | 2400 - 2500 | 4900 - 7125 | 1164 - 1279 |
| VSWR | 2.0 | | | 1.5 |
| Impedance (Ohm) | 50 | | | 50 |
| Gain (dBi) | 5 | | | |
| Composite power max (W) | 40 | | | |
| Ambient temperature (°C) | 25 | | | |
| Port isolation (dB) | 20 | | | |

Ports

| | Port 1 to 2 | Port 3 |
|------------------|-------------------|------------------|
| Port name | Tetra 1-2 (white) | GNSS (black) |
| Connector | N, plug (male) | TNC, plug (male) |
| Cable Type | ENVIROFLEX_316_D | ENVIROFLEX_316_D |
| Cable Length (m) | 0.5 | 0.5 |
| Polarization | Vertical | Circular right |
| DC Grounded | Yes | No |

Connections

| | Band 1 | Band 2 | Band 3 | Band 4 | Band 5 | Band 6 | Band 7 | Band 8 |
|-------------|--------|--------|--------|--------|--------|-------------|-------------|--------|
| Port 1 to 2 | X | X | X | X | X | (X: Band 3) | (X: Band 5) | |
| Port 3 | | | | | | | | X |

SENCITY® SC Omni-M 1399.99.0338

General Data

Ground plane: Indicated VSWR values are valid for a metallic ground plane of 0.5 x 0.5m or larger and Isolation is provided as typical values. Indicated VSWR values are mostly valid for installations on non-metallic surfaces also (no specific ground plane requirements). Indicated gain values will be achieved on a metallic ground plane of 1 x 1 m or larger.

Electrical Data LNA

| | |
|------------------------------|---------|
| LNA noise figure dB | 1.6 |
| LNA current consumption (mA) | 20 |
| LNA is connected to | Port 3 |
| LNA input voltage range: | 3..5V |
| Total gain @90° elevation: | 30 dBiC |

Mechanical Data

| | |
|-----------------------|------------------------------|
| Dimensions (mm) | 210 x 60 (Diameter x Height) |
| Weight (kg) | 1.1 |
| Mounting breakthrough | Ø30mm |

Environmental Data

| | |
|--|-------------|
| Environmental conditions | outdoor |
| Operation temperature (°C) | -40 to 85 |
| Storage temperature (°C) | -40 to 85 |
| Transport temperature (°C) | -40 to 85 |
| IP rating | IP68, IP69k |
| Solar radiation | DIN 75220 |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |
| REACH 1907/2006/EC | compliant |

Environmental tests: ETSI 300 019-4-2 class 4.1E
Low corrosion designed acc. to MIL-F-14072D
CE-Mark

Material Data

| | |
|--------------------------------|--------------------|
| Radome colour | RAL 9017 (black) |
| Radome material | PC (Polycarbonate) |
| Back plate/base plate material | Aluminium |

Related Products

(Order separately)
9091.99.0250 Metal ground plane foil 0.6x0.6m

Related Documents

| | |
|----------------------|----------------|
| Mounting instruction | DOC-0001171917 |
| Painting instruction | DOC-0000256180 |
| Security instruction | DOC-0000278984 |
| Outline drawing | DOU-01171893 |
| 3D-model | DOC-0001155892 |