

RADOX EN 50306-4 3E 300V MM S

Construc tion n x mm ²	Conductor nom. Dia mm	Core Dia. nom. mm	Screen Dia. mm	Cable dia. mm	R ₂₀ ²⁾ max. Ω/km	Fireload nom. kJ/m	Combustible material nom. kg/100m	Cable Weight nom. kg/100m	H + S Part No.
2x0.5	0.9	1.42	3.5	5.9±0.3	40.1	490	3.8	5.4	12586101
3x0.5	0.9	1.42	3.5	6.1±0.3	40.1	520	3.9	6.0	12586102
4x0.5	0.9	1.42	3.9	6.6±0.3	40.1	600	4.5	7.2	12586103
6x0.5	0.9	1.42	5.0	7.5±0.3	40.1	800	5.6	9.9	12586104
8x0.5	0.9	1.42	5.3	7.8±0.3	40.1	825	5.9	10.5	12586105
2x0.75	1.1	1.62	3.7	6.3±0.3	26.7	555	4.3	6.4	12586106
3x0.75	1.1	1.62	4.0	6.6±0.3	26.7	590	4.4	7.4	12586107
4x0.75	1.1	1.62	4.6	7.1±0.3	26.7	700	5.0	9.2	12586108
6x0.75	1.1	1.62	5.7	8.2±0.3	26.7	960	6.5	12.5	12586109
8x0.75	1.1	1.62	6.7	8.9±0.3	26.7	1080	7.4	15.0	12586110
2x1	1.2	1.77	4.0	6.6±0.3	20.0	595	4.6	7.2	12586111
3x1	1.2	1.77	4.4	6.9±0.3	20.0	660	4.8	8.5	12586112
4x1	1.2	1.77	4.8	7.2±0.3	20.0	670	5.0	9.5	12586113
6x1	1.2	1.77	5.9	8.35±0.3	20.0	900	6.5	13.4	12586114
8x1	1.2	1.77	7.0	9.0±0.3	20.0	1050	7.0	16.2	12586115
2x1.5	1.5	2.17	4.8	7.5±0.3	13.7	780	6.0	9.6	12586116
3x1.5	1.5	2.17	5.3	7.8±0.3	13.7	840	6.0	11.0	12586117
4x1.5	1.5	2.17	5.8	8.3±0.3	13.7	890	6.5	13.4	12586118
6x1.5	1.5	2.17	7.1	9.5±0.3	13.7	1245	8.5	17.5	12586119
8x1.5	1.5	2.17	8.7	11.1±0.3	13.7	1730	11.0	25.2	12586120
2x2.5	1.9	2.75	6.1	8.7±0.3	8.21	1040	7.6	13.6	12586121
3x2.5	1.9	2.75	6.5	8.9±0.3	8.21	1045	7.5	15.4	12586122
4x2.5	1.9	2.75	7.5	9.9±0.3	8.21	1280	9.0	19.3	12586123