

Data Sheet

SUCOFLEX_Stock Assembly

Description

The SUCOFLEX 102_E high end cable assemblies are designed to provide optimal performance up to 40 GHz where stringent electrical requirements – in particular stability and low loss, are important.

Product description PMASF102E/11SK/11SK/1219mm
Item number 85080280



Product Configuration

Cable type	SUCOFLEX_102_E
Length of assembly	1219 mm
Connector A	SK straight male
Connector B	SK straight male

Technical Data

Mechanical Data

Diameter:	4.0 mm
Min. bending radius static	12 mm
Min. bending radius repeated	20 mm
Recommended mating torque (*)	0.8...1.1 Nm

Environmental Data

Operating temperature	- 40°C to + 85°C
RoHS, REACH	Compliant

Electrical Data

Impedance	50 Ω
Operating frequency	up to 40 GHz
Velocity of propagation	77 %
Capacitance	87 pF / m
Time delay	4.3 ns / m

Return Loss	min. 14.9 dB	(up to 40 GHz)
Insertion loss (assembly)	max. 3.84 dB	(40 GHz, 25°C)
Phase matched, absolute	± 1.0 ps	
Power handling	min. 43 W	(40 GHz, sea level, 25°C)
Insertion loss stability vs. bending (**)	+/- 0.2 dB	(up to 40 GHz)
Phase stability vs. bending (**)	< 1.2°	(el/GHz)

General Information

(*) H+S torque wrench H+S description: 74_Z-0-0-21 // material/item number: 22543130
 (**) Stability test 360°, diameter 40 mm